

QUICK ACTION TAP COMPLETE WITH ELECTRONIC DIGITAL DISPLAY UNIT FOR USE WITH FMC 100 WITH TOP COVER



FMC 100/PP with top cover



Type	Quick Action Tap PP	Quick Action Tap PVDF
		
Flowrate	max. 50 l/min	max. 50 l/min
Operating pressure	max. 3 bar	max. 3 bar
Viscosity	max. 900 mPas (cP)	max. 900 mPas (cP)
Operating temperature	max. 50 °C	max. 50 °C
Inlet connection	DN 19	DN 19
Outlet tube	Ø 22 mm	Ø 22 mm
Material	Polypropylene (PP)	Polyvinylidenfluoride (PVDF)
Seal	FKM	FKM
Weight	0,5 kg	0,6 kg
Part No.	001 12 390	001 12 391

Type	Quick Action Tap MS	Quick Action Tap S
		
Flowrate	max. 80 l/min	max. 65 l/min
Operating pressure	max. 4 bar	max. 4 bar
Viscosity	max. 900 mPas (cP)	max. 900 mPas (cP)
Operating temperature	max. 80 °C	max. 80 °C
Inlet connection	Ø 32 mm	Ø 32 mm
Outlet tube	Ø 25 mm*	Ø 28 mm*
Material	Brass, nickel-plated (MS)	Stainless Steel 316 Ti (S)
Seal	PTFE	PTFE/FEP
Weight	1,5 kg	1,6 kg
Part No.	001 12 364	001 12 292

* Longer outlet tube Ø 20 mm for use with fume cone on request

Springer Pumps, LLC

Tel: 866-777-6060

Fax: 866-777-6383

info@springerpumps.com

www.springerpumps.com