



PRESSURE VALVES

BACK PRESSURE VALVES & PRESSURE RELIEF VALVES

PROTECT PROCESS SYSTEMS FROM
FLUCTUATING PRESSURE OR BLOCKAGE.



FEATURES & BENEFITS:

- CNC precision machined parts
- Pressure rated to 150 PSI (350 PSI also available)
- Cost efficient and reliable
- Variety of materials available
- Anti-syphon protection
- Optional air release and pressure gauge port on Back Pressure Valves
- Optional right-angle, 3-port design on Pressure Relief Valves



GET QUOTES QUICKLY ONLINE:

For quick and simple pricing requests, the SENTINEL Back Pressure Valves and Pressure Relief Valves are now available online at **Blacoh.com**. Visit the **SpeedQuote** to enter a part number and instantly get pricing or a spec-sheet drawing. Always conveniently available 24/7.



ABOUT

SENTINEL Back Pressure Valves

Blacoh Back Pressure Valves prevent siphoning and varying rates of dosage from fluctuating downstream pressure by enacting positive discharge pressure in your metering pump system.

SENTINEL Pressure Relief Valves

Blacoh Pressure Relief Valves operate when the system pressure raises above the set pressure of the valve to protect systems from damage due to blockages or excessive pressure situations.



Enhance the performance of pumping systems by applying a continuous back pressure to the system pump, while also acting as an anti-syphon valve.



Chemically resistant PTFE diaphragm comes standard on all units.



Robust construction ensures reliability in the rigorous service of municipal and industrial applications.

BLACOH FLUID CONTROL | 601 Columbia Ave., Bldg. D, Riverside, CA 92507

Tel: 866-777-6060
Fax: 866-777-6383

Springer Pumps, LLC

Website: www.springerpumps.com
Int'l: +001 267 404 2910

SENTINEL PRESSURE VALVES

Specifications

Max Flow Range @150 PSI				
VBP Part#	VPR Part#	Size	Pulsating US GPH	Continuous US GPM
VBP-025-*.**	VPR-025-*.**	1/4"	100	10
VBP-038-*.**	VPR-038-*.**	3/8"	200	15
VBP-049-*.**	VPR-049-*.**	1/2" (mini)	350	17.5
VBP-050-*.**	VPR-050-*.**	1/2" (std.)	500	25
VBP-075-*.**	VPR-075-*.**	3/4"	600	30
VBP-100-*.**	VPR-100-*.**	1"	600	30
VBP-150-*.**	VPR-150-*.**	1-1/2"	1350	67
VBP-200-*.**	VPR-200-*.**	2"	2000	100
(*) Body Material (ordering example: VBP-025-PP = 1/4" Polypropylene) PVC - PVC PVDF - Kynar PP - Polypropylene SS - 316 S.S. CPVC - CPVC A20 - Alloy 20 S.S. PTFE - PTFE H276 - HASTELLOY®				
(**) Diaphragm Material			T - PTFE, E - EPDM, V - VITON	
Pressure Range (PSI)			5-150 (50-350 PSI available on metal valves)	
Maximum Temperature			Plastic: 140° F, Metal: 300° F	
Material (Valve Top)			PVC, 316 S.S. or CPVC	

VBP= Valve, Back Pressure

VPR= Valve, Pressure Relief

Flanged and union connections also available.



All units are NSF ISO 9001:2008 Certified

Dimensions

Size (NPT)	A	B Dia.	C
Mini Body 1/4" to 1/2"	Metal: 3.85" Other: 4.25"	2.375"	1.125"
Std. Body 1/2" to 1"	5.75"	3.5"	1.25"
1-1/2"	9"	4.5"	2.125"
2"	9"	5"	2.125"

Larger sizes upon request.

CALIBRATION CYLINDERS

- Calibration columns & cylinders determine pump flow rate for metering pumps quickly and easily
- Enhance the performance of chemical feed systems
- Easy to read measurements in milliliters/minute and gallons/hour
- Robust construction of clear PVC and removable tops for cleaning



BLACOH FLUID CONTROL | 601 Columbia Ave., Bldg. D, Riverside, CA 92507

Part of the
BLACOH™
 FLUID CONTROL
 family of products

